








OZZIQUIP

AL20

	
TIPPING LOAD 800 kg	ENGINE POWER 22 hp

		
SPEED 10 km/h	FLOW RATE 33 l/min	LIFT HEIGHT 2.75 m

Technical Specifications

Model	AL20
Engine	Changchai 3m78
Hydrostatic Pump	PWG Italy
Power	16kW/22HP
Fuel	Diesel
Transmission	4WD Hydrostatic
Drive Speed	0-10 km/h
Auxiliary Hydraulic Flow	33 L/min
Hydrostatic Oil Flow	50 L/min
Max. Lift Height (Extended)	2.75 m
Max. Lift Height (Retracted)	2.27 m
Rated Lifting Capacity	500 kg
Min. Turning Radius	1980 mm
Max. Turning Angle	40 degrees
Operating Weight	1100 kg
Fuel Tank Capacity	18 L
Battery Capacity	55 Ah
Standard Tires	23x8.5-12
Overall Dimensions (L*W*H)	2195x980x2150

Standard Features

- 4WD Direct Drive Hydrostatic Motors
- Articulating Build
- DBS (Dynamic Block System)
- Self-levelling Telescopic Boom
- Hydraulic Multiconnector/ Quick Hitch
- Hydraulic Joystick
- Removable Steel Canopy
- Counterweights (3x 36kg)
- Fully Adjustable Seat
- Electrical Output
- 4 in 1 Bucket
- Dingo/Kanga/Boxer Quick Hitch System

Optional Attachments

There are over 60 attachments to choose from; each with its own unique application.

*Terms and Conditions apply.

Under our policy of continuous improvement, OZZIQUIP reserves the right to change technical data and design without prior notice.